



## IntelusCompact1

Compact Size Single Slot Atheros Network Platform

**Technical Specifications**

System Information

### System Information

<b>Radio Chip</b>	Atheros AR7130 300MHz Networking Processor
<b>Memory</b>	32MB ( 32 x 1 ) DDR SDRAM
<b>Flash</b>	8MB SPI Flash
<b>Mini-PCI Slot</b>	One Type-III Mini-PCI Slot
<b>Ethernet</b>	WAN 1 x 10/100 Base Ethernet Port (with Auto MDI/ MDIX) LAN 1 x 10/100 Base Ethernet Port (with Auto MDI/ MDIX)
<b>PoE</b>	Passive PoE (range: 12-18V DC) Input/ Output WAN Port PoE Input LAN Port PoE Output
<b>Push Button Reset/ WPS</b>	Yes
<b>Watch Dog Timer</b>	Yes
<b>GPIO (RS232/ I2C/ PCM)</b>	12 Pins Header
<b>JTAG Debug Interface</b>	14 Pins Header
<b>High Speed USB Interface</b>	10 Pins Header (2 x USB Port)
<b>LED Header</b>	7 Pins Header
<b>DC Jack Input</b>	Range 12V to 18V@2A DC Voltage
<b>Power Consumption</b>	15W Max
<b>RoHS Compliance</b>	Yes
<b>Humidity</b>	5% to 98% non-condensing
<b>Temperature Range</b>	Operating Temperature: -40°C to +85°C Storage Temperature: -60°C to +150°C
<b>Dimension (in mm)</b>	91 x 91 (mm)
<b>Weight</b>	62g